

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-8. (Cancelled)

9. (Previously Presented) A method comprising:

scanning a nonvolatile memory medium to find a first memory block containing a header

indicating that the first memory block is the first memory block of an existing file

stored on the nonvolatile memory medium; and

finding a next memory block using a next block pointer stored in the header of the first

memory block, if the existing file comprises more memory blocks than the first memory

block, the existing file being opened upon completion of the finding.

10. (Previously Presented) The method of claim 9, further comprising repeating the finding step

until either all memory blocks comprising the file have been found or an error condition

occurs.

11. (Previously Presented) A method comprising:

scanning a nonvolatile memory medium in sizes of one predetermined logical block, the

nonvolatile memory medium storing an existing file;

for each logical block, reading a block header containing a magic number;

testing the magic number to determine whether the logical block is a valid block or a free

block, and if the logical block is a valid block, performing a comparison of a file name

encoded within the block header with a specified file name to be opened;

testing a flag within the block header to determine whether the logical block is the first block of the existing file, if the comparison produces a match; and returning to the scanning step with the next logical block until either the comparison produces a match or all the blocks have been tested, thereby indicating an error condition, the existing file being opened if the comparison produces a match.

12. (Previously Presented) A method comprising:

scanning a nonvolatile memory medium in sizes of one predetermined-sized logical block, the nonvolatile memory medium for storing a new file; for each logical block, reading a block header containing a magic number; testing the magic number to determine whether the logical block is a valid block or a free block, and if the logical block is a free block, modifying its block header to comprise a valid magic number, the name of the new file to be opened, and flags indicating whether the logical block is either the first block or the last block of the new file; and returning to the scanning step with the next logical block until either the testing step has identified a free block or all the blocks have been tested, thereby indicating an error condition, the new file being opened if the testing step has identified a free block.

13. (Previously Presented) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method, the method comprising:

scanning a nonvolatile memory medium to find a first memory block containing a header indicating that the first memory block is the first memory block of an existing file stored on the nonvolatile memory medium; and

finding a next memory block using a next block pointer stored in the header of the first memory block, if the existing file comprises more memory blocks than the first memory block, the existing file being opened upon completion of the finding.

14. (Previously Presented) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method, the method comprising:
- scanning a nonvolatile memory medium in sizes of one predetermined logical block the nonvolatile memory medium storing an existing file;
- for each logical block,
- reading a block header containing a magic number;
- testing the magic number to determine whether the logical block is a valid block or a free block, and if the logical block is a valid block, performing a comparison of a file name encoded within the block header with the specified file name to be opened;
- testing a flag within the block header to determine whether the logical block is the first block of the specified file, if the comparison produces a match; and
- returning to the scanning step with the next logical block until either the comparison produces a match or all the blocks have been tested, thereby indicating an error condition, the existing file being opened if said comparison produces a match.

15. (Previously Presented) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method, the method comprising:

scanning a nonvolatile memory medium in sizes of one predetermined-sized logical block,
the nonvolatile memory medium for storing a new file;

for each logical block,

reading a block header containing a magic number;

testing the magic number to determine whether the logical block is a valid block or a

free block, and if the logical block is a free block, modifying its block header to

comprise a valid magic number, the name of the file to be opened, and flags

indicating whether the logical block is either the first block or the last block of said

file; and

returning to the scanning step with the next logical block until either the testing step has

identified a free block or all the blocks have been tested, thereby indicating an error

condition, the new file being opened if said testing step has identified a free block.

16-19. (Cancelled)

20. (Previously Presented) An apparatus comprising:

means for scanning the nonvolatile memory medium to find a first memory block containing

a header indicating that the first memory block is the first memory block of an existing

file stored on the nonvolatile memory medium; and

means for finding a next memory block using a next block pointer stored in the header of the

first memory block, if the existing file comprises more than the first memory block, the

existing file being opened upon completion of said finding.

21. (Previously Presented) An apparatus comprising:

scanning means for scanning a nonvolatile memory medium to find a first memory block

containing a header indicating that the first memory block is the first memory block of an existing file; and

finding means for finding a next memory block using a next block pointer stored in the

header of the first memory block, if the file comprises more than the first memory

block, the finding means operating iteratively until either all memory blocks of which

the existing file is comprised have been found or an error condition occurs, the existing

file being opened if all memory blocks of which the existing file is comprised have been

found.

22. (Previously Presented) An apparatus comprising:

scanning means for scanning a nonvolatile memory medium in sizes of one predetermined

logical block, the nonvolatile memory medium for storing a new file;

reading means for reading a block header containing a magic number for each logical block;

testing means for testing the magic number to determine whether the logical block is a valid

block or a free block, and if the logical block is a valid block, performing a comparison

of a file name encoded within the block header with a specified file name to be opened;

and

checking means for checking a flag within the block header to determine whether the logical

block is the first block of the existing file, if the comparison performed by the testing

means produces a match,

said scanning means operating iteratively on until either the comparison produces a match or

all the blocks have been tested, thereby indicating an error condition, the new file being

opened if the comparison produces a match.

23. (Previously Presented) An Apparatus comprising:

scanning means for scanning a nonvolatile memory medium in sizes of one predetermined

logical block, the nonvolatile memory medium for storing a new file;

reading means for reading a block header containing a magic number for each logical block;

testing means for testing the magic number to determine whether the logical block is a valid

block or a free block, and if the logical block is a free block, modifying the block

header to comprise a valid magic number, the name of the file to be opened, and flags

indicating whether the logical block is either the first block or the last block of the new

file,

the scanning means operating iteratively on next logical blocks until either the testing means

has identified a free block or all the blocks have been tested, thereby indicating an error

condition, the new file being opened if said testing means has identified a free block.

24. (Previously Presented) An apparatus comprising:

nonvolatile memory medium means for storing information in the form of a file;

scanning means for scanning memory blocks of the nonvolatile memory medium means to

find a first memory block of a selected file, the first memory block containing a header

having an indicator that indicates that it is the first memory block of the selected file;

and

finding means for finding a next memory block using a next block pointer stored in the

header for selected files having more than one memory block, the selected file being

opened upon completion of the finding.

25. (Previously Presented) The apparatus of claim 24, wherein the finding means operates iteratively until either all memory blocks of the selected file have been found or an error condition occurs.